


	<b>AVL Supermicro server platform Memory Module Qualification Test</b>		
	Intel E5-2650(SNB-EP) x 2, Intel C602	Test Results	<b>Pass</b>
	PN: KVR13E9/8HM (8GB / UDIMM ECC / ECC ) On: X9DRL-iF Rev.0		

RP77D3x-106-KI-SQ-SMC-V1		Module Information		Rev 01/07/2011
AVL WorkOrder #	wc3672	AVL A#	7816	
Start Date	5/11/2012	End Date	5/14/2012	
Tested By	Van N.			
Module Manufacturer	Kingston			
Module Part Number	KVR13E9/8HM			
Module BOM Number	9965525-026.A00LF			
Module Capacity / Memory Type / ECC	8GB / UDIMM ECC/ ECC			
Module Configuration (Width, # of devices, # of Ranks)	1Gx72 /18 Devices / 2 Ranks			
Speed Tested (Data rate of Mbps, CL-tRP-tRCD)	DDR3L-1333 /9-9-9			
DRAM Device Vendor	Hynix			
DRAM Device Part Number / Date code	H5TC4G83MFR-H9A		1209	
DRAM Die Revision / Process Technology ( nm )	M			
DRAM Device Config (Density / Width)	4Gbit / x8		512Mx8bit	
Thermal Sensor Device Vendor / Part Number / Revision	N/A			
Register Device Vendor / Part Number / Revision	N/A		N/A	



Platform System Information				
Motherboard Info (Model# & MB Revision & MB S/N & AVL S/N)	X9DRL-iF	0	0	SN1029
BIOS Revision / BIOS Date	1	2/21/2012		
CPU / Speed	Intel E5-2650(SNB-EP) x 2	2.0GHz		
Chipset info (Stepping)	Intel C602			



## AVL Supermicro server platform Memory Module Qualification Test

Intel E5-2650(SNB-EP) x 2, Intel C602

PN: KVR13E9/8HM (8GB / UDIMM ECC / ECC ) On: X9DRL-iF Rev.0

**Test Results:**

PASS

*Comments:*

### AVL Memory Module Qual Test Results Summary

Test # and name	Test Description	Specs	Test Results	Comments
<b>1. Latest BIOS Upgrade &amp; Configuration</b>	Download / Upgrade latest BIOS & record size and speed detection		Pass	
<b>2. SPD Check</b>	Memory module SPD content check for JEDEC compliance	JEDEC	Pass	Use proprietary tools
<b>3. Reset Cycle</b>	Run Linux based diags & utility software @ 50°C	50 loops	N/A	1 DIMM Per Channel when applicable
<b>4a. Stress Application Test</b>	Run Linux based diags & utility software @50°C	8 Hour per config	Pass	DIMM Loading per spec
<b>4b. Stream Benchmark Test</b>		5 loop per config	Pass	DIMM Loading per spec
<b>4b. Reset Cycle</b>		200 loop per config	Pass	DIMM Loading per spec
<b>5. Functional Stress Test</b>	Memory Stress Test @50°C -	12hrs	Pass	DIMM Loading per spec
<b>6. Stress Application Test</b>	Run Linux based diags & utility software @50°C	6hrs	N/A	3 DIMM Per Channel when applicable

Note: All test under IMC Vdd=Nom, Vref=Vddnom/2