



**Intel PCSD Server Memory Compatibility Test Certificate**

Test System: <b>Intel S2600CP (Canoe Pass)</b>	Test Result: <b>Pass</b>
------------------------------------------------	--------------------------

Leveraged System(s): N/A

Module Information									
RPXXXXXXXXXXXXXXXXXXXX Rev. 03/01/2014									
DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KVR16LE11S8/4I	UDIMM ECC	1.35V	4GB	512Mx72	1600	11	D	SR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
Hynix	H5TC4G83BFR-PBA	4Gb	512Mx8bit	1444			(512Mx8)*72		

  

Leveraged Memory Modules						
Vendor	Type	Voltage	CL	Speed		
1 Kingston	KVR16E11S8/4I	UDIMM ECC	1.5V	11	1600	
2						
3						
4						
5						
6						

System Configuration		
SETUP	System #1	System #2
AVL S/N	SN2311	SN6442
System S/N	QSCP13800398	QSCP14800221
Board Rev. (PBA)	E99552-401	G50768-501
CPU Type	E5-2680 v2 / 2.8 GHz	
Chipset	Intel C602	
BIOS / Date	02.03.0003 / 04/19/2014	
BMC / ME	01.21.6038 / 02.01.07.328	
FUR/SDR	1.10	
OS	Windows 2008 Enterprise R2 64bit SP1	
Test Tool	iWVSS 2.5.3, SELViewer, Pvmode2, Syscfg, WinPIRA, MemPuller	

Testing Summary		
Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Memory Stress	Test for 6 hours @ Max and Min Loading	HVDD Hot <span style="color: blue;">Pass</span>
4. Memory Stress		HVDD Cold <span style="color: blue;">Pass</span>
5. Memory Stress		LVDD Hot <span style="color: blue;">Pass</span>
6. Memory Stress		LVDD Cold <span style="color: blue;">Pass</span>
Note:		

Memory Module Image							
AVL USE ONLY:							
Completed by:	Andy Chang	Completion Date:	01/27/2015	AVL A#	A10338	AVL W/O	WD2912
Comments:							

Test Results

4C						
Minimum Loading						
Start Date		1/25/2015				
DIMM Voltage		1.5v				
DIMM	S/N	A	B	C	D	
CPU1 A1	SV6323	P	P	P	P	
CPU1 A2						
CPU1 B1	SV6324	P	P	P	P	
CPU1 B2						
CPU1 C1	SV6325	P	P	P	P	
CPU1 C2						
CPU1 D1	SV6326	P	P	P	P	
CPU1 D2						
CPU2 E1	SV6327	P	P	P	P	
CPU2 E2						
CPU2 F1	SV6328	P	P	P	P	
CPU2 F2						
CPU2 G1	SV6329	P	P	P	P	
CPU2 G2						
CPU2 H1	SV6208	P	P	P	P	
CPU2 H2						

4C						
Maximum Loading						
Start Date		1/25/2015				
DIMM Voltage		1.5v				
DIMM	S/N	A	B	C	D	
CPU1 A1	SV6307	P	P	P	P	
CPU1 A2	SV6308	P	P	P	P	
CPU1 B1	SV6309	P	P	P	P	
CPU1 B2	SV6310	P	P	P	P	
CPU1 C1	SV6311	P	P	P	P	
CPU1 C2	SV6312	P	P	P	P	
CPU1 D1	SV6313	P	P	P	P	
CPU1 D2	SV6314	P	P	P	P	
CPU2 E1	SV6315	P	P	P	P	
CPU2 E2	SV6316	P	P	P	P	
CPU2 F1	SV6317	P	P	P	P	
CPU2 F2	SV6318	P	P	P	P	
CPU2 G1	SV6319	P	P	P	P	
CPU2 G2	SV6320	P	P	P	P	
CPU2 H1	SV6321	P	P	P	P	
CPU2 H2	SV6207	P	P	P	P	



4C						
Minimum Loading						
Start Date		1/22/2015				
DIMM Voltage		1.35v				
DIMM	S/N	E	F	G	H	
CPU1 A1	SV6323	P	P	P	P	
CPU1 A2						
CPU1 B1	SV6324	P	P	P	P	
CPU1 B2						
CPU1 C1	SV6325	P	P	P	P	
CPU1 C2						
CPU1 D1	SV6326	P	P	P	P	
CPU1 D2						
CPU2 E1	SV6327	P	P	P	P	
CPU2 E2						
CPU2 F1	SV6328	P	P	P	P	
CPU2 F2						
CPU2 G1	SV6329	P	P	P	P	
CPU2 G2						
CPU2 H1	SV6330	P	P	P	P	
CPU2 H2						

4C						
Maximum Loading						
Start Date		01/22/15				
DIMM Voltage		1.35v				
DIMM	S/N	E	F	G	H	
CPU1 A1	SV6307	P	P	P	P	
CPU1 A2	SV6308	P	P	P	P	
CPU1 B1	SV6309	P	P	P	P	
CPU1 B2	SV6310	P	P	P	P	
CPU1 C1	SV6311	P	P	P	P	
CPU1 C2	SV6312	P	P	P	P	
CPU1 D1	SV6313	P	P	P	P	
CPU1 D2	SV6314	P	P	P	P	
CPU2 E1	SV6315	P	P	P	P	
CPU2 E2	SV6316	P	P	P	P	
CPU2 F1	SV6317	P	P	P	P	
CPU2 F2	SV6318	P	P	P	P	
CPU2 G1	SV6319	P	P	P	P	
CPU2 G2	SV6320	P	P	P	P	
CPU2 H1	SV6321	P	P	P	P	
CPU2 H2	SV6322	P	P	P	P	

