



**Intel PCSD Server Memory Compatibility Test Certificate**

Test System: <b>Intel S2600CP (Canoe Pass)</b>	Test Result: <b>Pass</b>
--	--------------------------

Leveraged System(s): N/A

Module Information									
RPXXXXXXXXXXXXXXXXXXXX									
Rev. 03/01/2014									
DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KVR16LR11D4/16I	RDIMM	1.35V	16GB	2Gx72	1600	11	E	DR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
Hynix	H5TC4G43BFR-PBA	4Gb	1024Mx4bit	1438	Inphi	GS02	(1024Mx4)X2*72		

System Configuration		
SETUP	System #1	System #2
AVL S/N	SN2311	SN6442
System S/N	QSCP13800398	QSCP14800221
Board Rev. (PBA)	E99552-401	G50768-501
CPU Type	E5-2680 v2 / 2.8 GHz	
Chipset	Intel C602	
BIOS / Date	02.03.0003 / 04/19/2014	
BMC / ME	01.21.6038 / 02.01.07.328	
FUR/SDR	1.10	
OS	Windows 2008 Enterprise R2 64bit SP1	
Test Tool	iWVSS 2.5.3, SELViewer, Pvmode2, Syscfg, WinPIRA, MemPuller	

Testing Summary		
Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Memory Stress	Test for 6 hours @ Max and Min Loading	HVDD Hot <span style="color: blue;">Pass</span>
4. Memory Stress		HVDD Cold <span style="color: blue;">Pass</span>
5. Memory Stress		LVDD Hot <span style="color: blue;">Pass</span>
6. Memory Stress		LVDD Cold <span style="color: blue;">Pass</span>
Note:		

Memory Module Image							
AVL USE ONLY:							
Completed by:	Andy Chang	Completion Date:	12/20/2014	AVL A#	A10270	AVL W/O	WD2649
Comments:							

Test Results

4C						
Minimum Loading						
Start Date		12/3/2014				
DIMM Voltage		1.5v				
DIMM	S/N	A	B	C	D	
CPU1 A1	SV4417	P	P	P	P	
CPU1 A2						
CPU1 B1	SV4418	P	P	P	P	
CPU1 B2						
CPU1 C1	SV4419	P	P	P	P	
CPU1 C2						
CPU1 D1	SV4420	P	P	P	P	
CPU1 D2						
CPU2 E1	SV4421	P	P	P	P	
CPU2 E2						
CPU2 F1	SV4422	P	P	P	P	
CPU2 F2						
CPU2 G1	SV4423	P	P	P	P	
CPU2 G2						
CPU2 H1	SV4430	P	P	P	P	
CPU2 H2						

4C						
Maximum Loading						
Start Date		12/03/14				
DIMM Voltage		1.5v				
DIMM	S/N	A	B	C	D	
CPU1 A1	SV4401	P	P	P	P	
CPU1 A2	SV4402	P	P	P	P	
CPU1 B1	SV4403	P	P	P	P	
CPU1 B2	SV4404	P	P	P	P	
CPU1 C1	SV4405	P	P	P	P	
CPU1 C2	SV4406	P	P	P	P	
CPU1 D1	SV4407	P	P	P	P	
CPU1 D2	SV4408	P	P	P	P	
CPU2 E1	SV4409	P	P	P	P	
CPU2 E2	SV4410	P	P	P	P	
CPU2 F1	SV4411	P	P	P	P	
CPU2 F2	SV4412	P	P	P	P	
CPU2 G1	SV4413	P	P	P	P	
CPU2 G2	SV4414	P	P	P	P	
CPU2 H1	SV4415	P	P	P	P	
CPU2 H2	SV4430	P	P	P	P	

4C						
Minimum Loading						
Start Date		12/2/2014				
DIMM Voltage		1.35v				
DIMM	S/N	E	F	G	H	
CPU1 A1	SV4417	P	P	P	P	
CPU1 A2						
CPU1 B1	SV4418	P	P	P	P	
CPU1 B2						
CPU1 C1	SV4419	P	P	P	P	
CPU1 C2						
CPU1 D1	SV4420	P	P	P	P	
CPU1 D2						
CPU2 E1	SV4421	P	P	P	P	
CPU2 E2						
CPU2 F1	SV4422	P	P	P	P	
CPU2 F2						
CPU2 G1	SV4423	P	P	P	P	
CPU2 G2						
CPU2 H1	SV4424	P	P	P	P	
CPU2 H2						

4C						
Maximum Loading						
Start Date		12/05/14				
DIMM Voltage		1.35v				
DIMM	S/N	E	F	G	H	
CPU1 A1	SV4401	P	P	P	P	
CPU1 A2	SV4402	P	P	P	P	
CPU1 B1	SV4403	P	P	P	P	
CPU1 B2	SV4404	P	P	P	P	
CPU1 C1	SV4405	P	P	P	P	
CPU1 C2	SV4406	P	P	P	P	
CPU1 D1	SV4407	P	P	P	P	
CPU1 D2	SV4408	P	P	P	P	
CPU2 E1	SV4409	P	P	P	P	
CPU2 E2	SV4410	P	P	P	P	
CPU2 F1	SV4411	P	P	P	P	
CPU2 F2	SV4412	P	P	P	P	
CPU2 G1	SV4413	P	P	P	P	
CPU2 G2	SV4414	P	P	P	P	
CPU2 H1	SV4415	P	P	P	P	
CPU2 H2	SV4416	P	P	P	P	