



Advanced Validation Labs, Inc.
17665B Newhope Street, Fountain Valley, CA 92708 (714) 435-2630



Intel PCSD Server Memory Compatibility Test Certificate	
Test System: Intel S2600JF (Jefferson Pass)	Test Result: Pass

Leveraged System(s): N/A


Module Information									
DIMM Vendor	DIMM Part Number	Type	Voltage	Size	Config.	Speed	CL	R/C	Rank
Kingston	KVR16LR11D8/8I	RDIMM	1.35V	8GB	1Gx72	1600	11	B	DR
DRAM Vendor	DRAM Part Number	DRAM Density / Width / Date Code			Register Vendor / Rev.		DIMM Composition		
Hynix	HTC4G83BFR-PBA	4Gb	512Mx8bit	1452	IDT	A	(512Mx8)x2*72		

Leveraged Memory Modules						
	Vendor	Type	Voltage	CL	Speed	
1	Kingston	KVR16LR11D8K3/24I	RDIMM	1.35V	11	1600
2	Kingston	KVR16LR11D8K4/32I	RDIMM	1.35V	11	1600
3	Kingston	KVR16R11D8/8I	RDIMM	1.5V	11	1600
4	Kingston	KVR16R11D8K3/24I	RDIMM	1.5V	11	1600
5	Kingston	KVR16R11D8K4/32I	RDIMM	1.5V	11	1600
6						

System Configuration		
SETUP	System #1	System #2
AVL S/N	SR4140	SN5652
System S/N	QSJP13704142	QSJP13704121
Board Rev. (PBA)	G28033-501	
CPU Type	E5-2695 v2 / 2.4 GHz	
Chipset	Intel C602	
BIOS / Date	02.03.0003 / 04/19/2014	
BMC / ME	01.21.6038 / 02.01.07.328	
FUR/SDR	1.10	
OS	Windows 2008 Enterprise R2 64bit SP1	
Test Tool	iWVSS 2.5.3, SELViewer, Pvmode2, Syscfg, WinPIRA, MemPuller	

Testing Summary		
Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Memory Stress	Test for 6 hours @ Max and Min Loading	HVDD Hot
4. Memory Stress		HVDD Cold
5. Memory Stress		LVDD Hot
6. Memory Stress		LVDD Cold
Note:		

Memory Module Image



AVL USE ONLY:							
Completed by:	Andy Chang	Completion Date:	03/13/15	AVL A#	A10433	AVL W/O	WD3189
Comments:							

Test Results

4C					
Maximum Loading					
Start Date		3/9/2015			
DIMM Voltage		1.5v			
DIMM	S/N	A	B	C	D
CPU1 A1	SV8944	P	P	P	P
CPU1 B1	SV8945	P	P	P	P
CPU1 C1	SV8946	P	P	P	P
CPU1 D1	SV8947	P	P	P	P
CPU2 E1	SV8948	P	P	P	P
CPU2 F1	SV8949	P	P	P	P
CPU2 G1	SV8950	P	P	P	P
CPU2 H1	SV9037	P	P	P	P

4C					
Maximum Loading					
Start Date		2/17/2015			
DIMM Voltage		1.35v			
DIMM	S/N	E	F	G	H
CPU1 A1	SV8944	P	P	P	P
CPU1 B1	SV8945	P	P	P	P
CPU1 C1	SV8946	P	P	P	P
CPU1 D1	SV8947	P	P	P	P
CPU2 E1	SV8948	P	P	P	P
CPU2 F1	SV8949	P	P	P	P
CPU2 G1	SV8950	P	P	P	P
CPU2 H1	SV8951	P	P	P	P