

	<b>AVL Supermicro server platform Memory Module Qualification Test</b>		
	Intel E5-2650(IVB) x 2, Intel C602	Test Results	<b>Pass</b>
	PN: KVR16R11D8/8KF (8GB / RDIMM / ECC ) On: X9DAI Rev.1234567890		

RP77D3x-106-KI-SQ-SMC-V2		Module Information		Rev 05/30/2012
AVL WorkOrder #	WC9587	AVL A#	9649	
Start Date	1/30/2014	End Date	1/31/2014	
Tested By	Van N.			
Module Manufacturer	Kingston			
Module Part Number	KVR16R11D8/8KF			
Module BOM Number	9965426-169.A00LF			
Module Capacity / Memory Type / ECC	8GB / RDIMM / ECC			
Module Configuration (Width, # of devices, # of Ranks)	1Gx72 /18 Devices / 2 Ranks			
Speed Tested (Data rate of Mbps, CL-tRP-tRCD)	DDR3-1600 /11-11-11			
DRAM Device Vendor	Kingston			
DRAM Device Part Number / Date code	D5128ED1FPGGB			1345
DRAM Die Revision / Process Technology ( nm )	F			
DRAM Device Config (Density / Width)	512Mbit / x8 /512Mx8bit			
Thermal Sensor Device Vendor / Part Number / Revision	On-Semi			
Register Device Vendor / Part Number / Revision	Montage	SSTE32882	1.0	



Platform System Information				
Motherboard Info (Model# & MB Revision & MB S/N & AVL S/N)	X9DAI	1234567890	UM23S30507	SN9376
BIOS Revision / BIOS Date	3.0		8/5/2013	
CPU / Speed	Intel E5-2650(IVB) x 2		2.6GHz	
Chipset info (Stepping)	Intel C602			

	<b>AVL Supermicro server platform Memory Module Qualification Test</b>
	Intel E5-2650(IVB) x 2, Intel C602 PN: KVR16R11D8/8KF (8GB / RDIMM / ECC ) On: X9DAI Rev.1234567890

<b>Test Results:</b>	<b>PASS</b>
<i>Comments:</i>	

### AVL Memory Module Qual Test Results Summary

Test # and name	Test Description	Specs	Test Results	Comments
<b>1. Latest BIOS Upgrade &amp; Configuration</b>	Download / Upgrade latest BIOS & record size and speed detection		Done	
<b>2. SPD Check</b>	Memory module SPD content check for JEDEC compliance	JEDEC	Pass	Use proprietary tools
<b>3. Reset Cycle</b>	Run Linux based diags & utility software @ 55°C	50 loops	Pass	1 DIMM Per Channel when applicable
<b>4a. Stress Application Test</b>	Run Linux based diags & utility software @55°C	8 Hour per config	Pass	DIMM Loading per spec
<b>4b. Stream Benchmark Test</b>		5 loop per config	Pass	DIMM Loading per spec
<b>4b. Reset Cycle</b>		200 loop per config	Pass	DIMM Loading per spec
<b>5. Functional Stress Test</b>	Memory Stress Test @55°C	12hrs	Pass	DIMM Loading per spec
<b>6. Stress Application Test</b>	Run Linux based diags & utility software @55°C	8hrs	N/A	3 DIMM Per Channel when applicable

Note: All test under IMC Vdd=Nom, Vref=Vddnom/2